



Lead Thickness Chart

Fraction	Decimal	MM	Lbs / SF
1/64"	0.01563"	0.40	0.92
1/59"	0.01695"	0.43	1.00
1/32"	0.03125"	0.79	1.84
2/59"	0.03390"	0.86	2.00
3/64"	0.04688"	1.19	2.77
3/59"	0.05085"	1.29	3.00
1/16"	0.06250"	1.59	3.69
4/59"	0.06780"	1.72	4.00
5/64"	0.07813"	1.98	4.61
5/59"	0.08475"	2.15	5.00
3/32"	0.09375"	2.38	5.53
6/59"	0.10169"	2.58	6.00
7/64"	0.10938"	2.78	6.45
7/59"	0.11864"	3.01	7.00
1/8"	0.12500"	3.18	7.38
8/59"	0.13559"	3.44	8.00
9/64"	0.14063"	3.57	8.30
9/59"	0.15254"	3.87	9.00
5/32"	0.15625"	3.97	9.22
10/59"	0.16949"	4.31	10.00
11/64"	0.17188"	4.37	10.14
11/59"	0.18644"	4.74	11.00
3/16"	0.18750"	4.76	11.06
13/64"	0.20313"	5.16	11.98
12/59"	0.20339"	5.17	12.00
7/32"	0.21875"	5.56	12.91
13/59"	0.22034"	5.60	13.00
15/64"	0.23438"	5.95	13.83
14/59"	0.23729"	6.03	14.00
1/4"	0.25000"	6.35	14.75
15/59"	0.25424"	6.46	15.00
17/64"	0.26563"	6.75	15.67
16/59"	0.27119"	6.89	16.00
9/32"	0.28125"	7.14	16.59
17/59"	0.28814"	7.32	17.00
19/64"	0.29688"	7.54	17.52
18/59"	0.30508"	7.75	18.00
5/16"	0.31250"	7.94	18.44
19/59"	0.32203"	8.18	19.00
21/64"	0.32813"	8.33	19.36
20/59"	0.33898"	8.61	20.00
11/32"	0.34375"	8.73	20.28
21/59"	0.35593"	9.04	21.00
23/64"	0.35938"	9.13	21.20
22/59"	0.37288"	9.47	22.00
3/8"	0.37500"	9.53	22.13
23/59"	0.38983"	9.90	23.00
25/64"	0.39063"	9.92	23.05
13/32"	0.40625"	10.32	23.97
24/59"	0.40678"	10.33	24.00
27/64"	0.42188"	10.72	24.89
25/59"	0.42373"	10.76	25.00
7/16"	0.43750"	11.11	25.81
26/59"	0.44068"	11.19	26.00
29/64"	0.45313"	11.51	26.73
27/59"	0.45763"	11.62	27.00
15/32"	0.46875"	11.91	27.66
28/59"	0.47458"	12.05	28.00
31/64"	0.48438"	12.30	28.58
29/59"	0.49153"	12.48	29.00
1/2"	0.50000"	12.70	29.50

Fraction	Decimal	MM	Lbs / SF
30/59"	0.50847"	12.92	30.00
33/64"	0.51563"	13.10	30.42
31/59"	0.52542"	13.35	31.00
17/32"	0.53125"	13.49	31.34
32/59"	0.54237"	13.78	32.00
35/64"	0.54688"	13.89	32.27
33/59"	0.55932"	14.21	33.00
9/16"	0.56250"	14.29	33.19
34/59"	0.57627"	14.64	34.00
37/64"	0.57813"	14.68	34.11
35/59"	0.59322"	15.07	35.00
19/32"	0.59375"	15.08	35.03
39/64"	0.60938"	15.48	35.95
36/59"	0.61017"	15.50	36.00
5/8"	0.62500"	15.88	36.88
37/59"	0.62712"	15.93	37.00
41/64"	0.64063"	16.27	37.80
38/59"	0.64407"	16.36	38.00
21/32"	0.65625"	16.67	38.72
39/59"	0.66102"	16.79	39.00
43/64"	0.67188"	17.07	39.64
40/59"	0.67797"	17.22	40.00
11/16"	0.68750"	17.46	40.56
41/59"	0.69492"	17.65	41.00
45/64"	0.70313"	17.86	41.48
42/59"	0.71186"	18.08	42.00
23/32"	0.71875"	18.26	42.41
43/59"	0.72881"	18.51	43.00
47/64"	0.73438"	18.65	43.33
44/59"	0.74576"	18.94	44.00
3/4"	0.75000"	19.05	44.25
45/59"	0.76271"	19.37	45.00
49/64"	0.76563"	19.45	45.17
46/59"	0.77966"	19.80	46.00
25/32"	0.78125"	19.84	46.09
47/59"	0.79661"	20.23	47.00
51/64"	0.79688"	20.24	47.02
13/16"	0.81250"	20.64	47.94
48/59"	0.81356"	20.66	48.00
53/64"	0.82813"	21.03	48.86
49/59"	0.83051"	21.09	49.00
27/32"	0.84375"	21.43	49.78
50/59"	0.84746"	21.53	50.00
55/64"	0.85938"	21.83	50.70
51/59"	0.86441"	21.96	51.00
7/8"	0.87500"	22.23	51.63
52/59"	0.88136"	22.39	52.00
57/64"	0.89063"	22.62	52.55
53/59"	0.89831"	22.82	53.00
29/32"	0.90625"	23.02	53.47
54/59"	0.91525"	23.25	54.00
59/64"	0.92188"	23.42	54.39
55/59"	0.93220"	23.68	55.00
15/16"	0.93750"	23.81	55.31
56/59"	0.94915"	24.11	56.00
61/64"	0.95313"	24.21	56.23
57/59"	0.96610"	24.54	57.00
31/32"	0.96875"	24.61	57.16
58/59"	0.98305"	24.97	58.00
63/64"	0.98438"	25.00	58.08
1"	1.00000"	25.40	59.00

Notes:

1. The lead thickness in pounds per square foot is based on actual weight per square foot - not nominal nor approximate!
2. Physicists sometimes list the lead thickness in both fraction of a inch and nominal (approximate) weight per square foot.
Example: They may list 1/16" and/or 4 lbs. But as you can see above they are not the same. If this occurs, please advise if you want us to quote per the inch thickness or the actual pound thickness you require.
3. We will supply lead equal to or greater than the lead thickness specified.